

This Page Is Inserted by IFW Operations
and is not a part of the Official Record

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

IMAGES ARE BEST AVAILABLE COPY.

**As rescanning documents *will not* correct images,
please do not report the images to the
Image Problem Mailbox.**

IN THE CLAIMS

The claims should now read as follows.

1. (Currently Amended) A medical catheter system comprising:
 - a first catheter having
 - an entrance orifice,
 - an exit orifice,
 - a channel connecting the entrance orifice and the exit orifice,
 - a wall surrounding the channel,
 - the hardness of the wall surrounding the channel decreasing in hardness in a first distinct region then increasing in hardness in a second distinct region and then decreasing in hardness again in a third distinct region, regardless of the orientation of the wall, when considered from an initial reference point at the entrance orifice and traveling towards the exit orifice and,
 - a second catheter located within the first catheter, the first catheter sized to allow the second catheter to move within it, the second catheter having a steerable distal portion.
2. (Canceled)
3. (Original) The medical catheter system of claim 2 further comprising:
 - a third catheter located within the second catheter, the second catheter sized to allow the third catheter to move within it.
4. (Original) The medical catheter system of claim 2 wherein the second catheter has a plurality of flushing orifices sized to allow fluid to pass from an outside surface of the second catheter to an inside surface of the second catheter.
5. (Original) The medical catheter system of claim 2 wherein the second catheter has a bendable curve memory portion.

6. (Previously Presented) The medical catheter system of claim 5 wherein the bendable curve memory portion of the second catheter contains a cross-linking polymer activated by ultra-violet light, when activated the curve memory portion becoming shaped into a predetermined shape.
7. (Original) The medical catheter system of claim 5 wherein the bendable curve memory portion of the second catheter contains an outer layer with a first hardness and an inner layer with a second hardness, the second hardness being harder than the first hardness.
8. (Original) The medical catheter system of claim 2 wherein the second catheter has an outer layer with a first hardness and an inner layer with a second hardness, the second hardness being harder than the first hardness.
9. (Previously Presented) A medical catheter system comprising:
 - a first steerable guide catheter having
 - an entrance orifice,
 - an exit orifice, and
 - a first wall surrounding a channel linking the entrance orifice and the exit orifice, the first wall having a bendable curve memory portion.
10. (Previously Presented) The medical catheter system of claim 9 wherein the bendable curve memory portion is bent into a predetermined shape and contains a plurality of flushing orifices.
11. (Currently Amended) The medical catheter system of claim 9 wherein the first wall contains a reinforcing structure and the bendable curve memory portion comprises a curve memory material.
12. (Original) The medical catheter system of claim 9 wherein an inside surface of the first

catheter includes a lubricious treatment.

13. (Withdrawn) The medical catheter system of claim 9 further comprising:

a second catheter,

the second catheter surrounding the first catheter,

the second catheter having an entrance orifice, an exit orifice,

and a second wall surrounding a second channel linking the entrance orifice and exit orifice of the second catheter,

the hardness of the second wall surrounding the channel of the second catheter decreasing in hardness then increasing in hardness and then decreasing in hardness again when considered from an initial reference point at the entrance opening and then traveling towards the exit opening.

14. (Withdrawn) The medical catheter system of claim 9 wherein the first catheter has a flushing orifice passing through the first wall, the flushing orifice sized to allow flushing fluid to pass between an outside surface of the first wall and an inside surface of the first wall.

15. (Withdrawn) The medical catheter system of claim 9 wherein the first catheter has an outer layer with a first hardness and an inner layer with a second hardness, the second hardness being harder than the first hardness.

16. (Withdrawn) The medical catheter system of claim 15 wherein the first catheter further comprises a third layer, the third layer located within the inner layer, the third layer having a hardness that is harder than the second layer.

17. (Withdrawn) A medical catheter system comprising:

an outer catheter;

an inner catheter,

the inner catheter sized to moveably fit within at least a portion of the outer

catheter,
the second inner catheter having a flushing orifice passing through a first wall of
the inner catheter,
the flushing orifice sized to allow flushing fluid to pass between an outside
surface of the first wall and an inside surface of the first wall; and
a flushing line, the flushing line coupled to the flushing orifice.

18. (Withdrawn) The medical system of claim 17 wherein the outer catheter has an entrance orifice, an exit orifice, a channel connecting the entrance orifice and the exit orifice, and a second wall surrounding the channel, the hardness of the second wall surrounding the channel decreasing in hardness then increasing in hardness and then decreasing in hardness again when considered from an initial reference point at the entrance orifice and traveling towards the exit orifice.

19. (Withdrawn) The medical catheter system of claim 17 wherein the inner catheter has a bendable curve memory portion.

20. (Withdrawn) The medical catheter system of claim 19 wherein the bendable curve memory portion of the inner catheter contains a cross-linking polymer activated by ultra-violet light.

21. (Withdrawn) The medical catheter system of claim 17 wherein the inner catheter contains an outer layer with a first hardness and an inner layer with a second hardness, the second hardness being harder than the first hardness.

22. (Withdrawn) The medical catheter system of claim 21 wherein the inner catheter further comprises a third layer, the third layer located within the second layer, the third layer having a hardness that is harder than the second layer.

23. (Withdrawn) A medical catheter system comprising:

a first catheter having an inner layer and an outer layer,
the inner layer having a first hardness and the outer layer having a second
hardness, the first hardness being harder than the second hardness.

24. (Withdrawn) The medical catheter system of claim 23 wherein the inner layer contains a reinforcing member.

25. (Withdrawn) The medical catheter system of claim 23 wherein the inner layer contains a lubricious treatment.

26. (Withdrawn) The medical catheter system of claim 23 further comprising:
a second catheter surrounding a portion of the first catheter,
the second catheter having
an entrance orifice, an exit orifice, a channel connecting the
entrance orifice and the exit orifice, and
a second wall surrounding the channel,
the hardness of the second wall surrounding the channel,
decreasing in hardness then increasing in hardness and then decreasing in hardness again when
considered from an initial reference point at the entrance orifice of the second catheter and
then traveling towards the exit orifice of the second catheter.

27. (Withdrawn) The medical catheter system of claim 23 wherein the first catheter has a
flushing orifice passing through the inner layer and the outer layer, the flushing orifice sized to
allow flushing fluid to pass between an outside surface of the outer layer and an inside surface of
the inner layer.

28. (Previously Presented) The medical catheter system of claim 9 wherein the steerable
guide catheter contains a first layer, a second layer, and a third layer, each layer having a different
hardness.